



LED

IP20

IP44



RD15 series recessed fixed low glare LED downlight designed with high efficacy COB LED chip, excellent glare control, powder coated aluminium housing with various reflector options and remote LED driver.

Colour Temperature: 2700K / 3000K / 4000K / 5000K

LEDs Life Time: 50,000Hrs L70 / B10

CRI: CRI80+, CRI90+, Cyanosis COI

Beam Angle: 15° / 24° / 38° / 55° / 60°

Driver options: Non-dimmable, Triac dimmable, DALI/DSI dimmable LED driver

IP Rating: IP20 / IP44

IC Rating: IC-4

Trim Colour: White finish

Reflector Colour: White, Black, Metalized

Applications:

Offices, Aged Care Facilities, Foyers, Hotels.

Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers.

*** NOTE: Dimensions and Cut Out sizes may change without notification

RD15 series recessed fixed downlight

Cat	Watt	Lumen output 4000K / 55°	CRI	Beam	Overall Size Diameter	Cut Out	IP
RD15-4	3.5W	520Lm	CRI80+	15° / 24° / 38° / 55°	Ø 100mm	90mm dia	IP20/IP44
RD15-6	5.5W	757Lm	CRI80+	15° / 24° / 38° / 55°	Ø 100mm	90mm dia	IP20/IP44
RD15-9	9.2W	895Lm	CRI80+	15° / 24° / 38° / 55°	Ø 100mm	90mm dia	IP20/IP44
RD15-11	10.9W	1152Lm	CRI80+	15° / 24° / 38° / 55°	Ø 100mm	90mm dia	IP20/IP44
RD15-15	15.2W	1644Lm	CRI80+	15° / 24° / 38° / 55°	Ø 100mm	90mm dia	IP20/IP44
RD15-17	17.5W	1681Lm	CRI80+	15° / 24° / 38° / 55°	Ø 100mm	90mm dia	IP20/IP44
RD15-20	21.4W	2115Lm	CRI80+	15° / 24° / 38° / 55°	Ø 100mm	90mm dia	IP20/IP44





Optional Extras

Suffix

RD15-11 10.9W LED 4000K, CRI80+, 55deg beam, White reflector, non-dimmable with IP44 lamp

Example: Specify as: **RD15-11 - (4K) - (C80) - (B55) - (WR) - (ND) - (IP44)**

CCT	CRI	Beam Angle	Reflector	Dimmable	Lamp's IP Rating
2K = 2700K 3K = 3000K 4K = 4000K 5K = 5000K	C80 = CRI80+ C90 = CRI90+ CY = Cyanosis	B15 = 15° B24 = 24° B38 = 38° B55 = 55°	WR = White reflector BR = Black reflector MR = Metalized reflector	ND = Non-dimmable DM = Triac dimmable EBD = DALI/DSI dimm	IP20 IP44



Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers.

*** NOTE: Dimensions and Cut Out sizes may change without notification