



RD25 series recessed fixed low glare LED downlight with high efficacy COB LED chip. Excellent glare control. Powder coated aluminium housing, remote LED driver.

<b><u>Colour Temperature:</u></b>	2700K / 3000K / 4000K / 5000K
<b><u>CRI:</u></b>	CRI80+, CRI90+, Cyanosis COI
<b><u>LEDs Life Time:</u></b>	50,000Hrs L70 / B10
<b><u>Beam Angle:</u></b>	from 15° up to 55°
<b><u>Driver options:</u></b>	Non-dimmable, Triac dimmable, DALI/DSI dimmable LED driver
<b><u>IP Rating:</u></b>	IP20 / IP44
<b><u>Trim Colour:</u></b>	White finish
<b><u>Lamp's Maintenance:</u></b>	Replaceable LED

**Applications:**

Offices, Hotels, Aged Care Facilities, Foyers

Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers.

\*\*\* NOTE: Dimensions and Cut Out sizes may change without notification

Cat	Watt	Lumen output	CRI	Beam	Overall Size Diameter X Height	Cut Out	IP
RD25-15	15W	1548Lm	CRI80+	20° / 30° / 38° / 55°	Ø160mm X 131mm	140mm dia	IP20/IP44
RD25-17	17W	1753Lm	CRI80+	15° / 24° / 38° / 55°	Ø160mm X 150mm	140mm dia	IP20/IP44
RD25-21	21W	2087Lm	CRI80+	15° / 24° / 38° / 55°	Ø160mm X 150mm	140mm dia	IP20/IP44
RD25-27	27W	2779Lm	CRI80+	15° / 24° / 38° / 55°	Ø160mm X 153mm	140mm dia	IP20/IP44
RD25-27H	27W	3355Lm	CRI80+	15° / 24° / 38° / 60°	Ø160mm X 148mm	140mm dia	IP20/IP44
RD25-35H	35W	4170Lm	CRI80+	15° / 24° / 38° / 60°	Ø160mm X 148mm	140mm dia	IP20/IP44





## Optional Extras

### Suffix

**RD25-18 18.3W LED 4000K, CRI80+, 38deg beam, non-dimmable with IP44 lamp**

**Example: Specify as: RD25-18 - (4K) - (C80) - (B38) - (ND) - (IP44)**

CCT	CRI	Beam Angle	LED Driver Options	IP Rating Options
2K = 2700K 3K = 3000K 4K = 4000K 5K = 5000K	C80 = CRI80+ C90 = CRI90+ CY = Cyanosis	B15 = 15° B20 = 20° B24 = 24° B30 = 30° B38 = 38° B55 = 55° B60 = 60°	ND = Non-dimmable DM = Triac Dimmable EBD = DALI or DSI Dimmable	IP20 IP44



Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers.

\*\*\* NOTE: Dimensions and Cut Out sizes may change without notification