Rytec Lighting Australia Pty Ltd





RDO44 series IP44 LED downlight with high efficacy and uniform distribution PC opal diffuser and powder coated aluminium housing and trim.

<u>Life Time:</u>	50,000Hrs L70 / B10				
<u>CRI:</u>	CRI80+				
<u>Beam Angle:</u>	90° beam angle				
<u>Colour Temperature:</u>	2700K, 3000K, 4000K, 5000K				
Driver options:	Non-dimmable, Triac dimmable, DALI/DSI dimmable				
<u>IP Rating:</u>	IP44				
Available Colour:	White finish				

Applications:

General lighting, Offices, Hotels, Aged Care Facilities, Bath rooms & Changing rooms

Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers. *** NOTE: Dimensions and Cut Out sizes may change without notificatio



Rytec Lighting Australia Pty Ltd

42 Volt Circuit, Dandenong South, VIC 3175 Ph: 03 9702 7213 E-mail: sales@ryteclighting.com.au

Copyright © [2020] Rytec Lighting Australia Pty Ltd. All rights reserved.

Rytec Lighting Australia Pty Ltd

Cat	Watt	Colour Temperature	Lumen Output	CRI	Beam	Size Dia x Height	Cut Out	PI
RDO44/110-13	13W	3000K 4000K	901 1320	80+ 80+	90°	110 x 40	Ø 95	IP44
RDO44/145-13	13W	3000K 4000K	1118 1325	80+ 80+	90°	145 x 45	Ø 125	IP44
RDO44/145-18	18W	3000K 4000K	1548 1867	80+ 80+	90°	145 x 45	Ø 125	IP44
RDO44/170-18	18W	3000K 4000K	1511 1615	80+ 80+	90°	170 x 45	Ø 145	IP44
RDO44/170-25	25W	3000K 4000K	2233 2392	80+ 80+	90°	170 x 45	Ø 145	IP44
RDO44/190-18	18W	3000K 4000K	1768 1956	80+ 80+	90°	190 x 45	Ø 165	IP44
RDO44/190-25	25W	3000K 4000K	2399 2633	80+ 80+	90°	190 x 45	Ø 165	IP44
RDO44/190-35	35W	3000K 4000K	2902 3472	80+ 80+	90°	190 x 45	Ø 165	IP44
RDO44/228-18	18W	3000K 4000K	1535 1712	80+ 80+	90°	228 x 45	Ø 205	IP44
RDO44/228-25	25W	3000K 4000K	2193 2497	80+ 80+	90°	228 x 55	Ø 205	IP44
RDO44/228-35	35W	3000K 4000K	3150 3383	80+ 80+	90°	228 x 55	Ø 205	IP44
RDO44/280-45	45W	3000K 4000K	4220 4346	80+ 80+	90°	280 x 552	Ø 240	IP44

Optional Extra

Options	Suffix	Comments
Triac Dimmable	DM	Triac dimmable LED driver
DALI / DSI Dimmable	EBD	DALI / DSI Dimmable LED driver









Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers. *** NOTE: Dimensions and Cut Out sizes may change without notificatio



42 Volt Circuit, Dandenong South, VIC 3175 Ph: 03 9702 7213 E-mail: sales@ryteclighting.com.au

Copyright © [2020] Rytec Lighting Australia Pty Ltd. All rights reserved.