



SYMMETRICAL



ASYMMETRICAL



RLDR437 series linear recessed low glare LED downlight designed with high efficacy COB LED chip, excellent glare control, powder coated aluminium housing and remote LED driver.

<u>Colour Temperature:</u>	2700K / 3000K / 4000K
<u>LEDs Life Time:</u>	50,000Hrs L70 / B10 at 25C°
<u>CRI:</u>	CRI90+
<u>Beam Angle:</u>	<u>Symmetrical:</u> 15° / 36° <u>Asymmetrical:</u> 70°x 90°x 10°
<u>Driver options:</u>	Non-dimmable, Triac dimmable, DALI dimmable LED driver
<u>Symmetrical series:</u>	UGR<19
<u>IP Rating:</u>	IP20
<u>Trim Colour:</u>	White or black finish

Applications:

Hotels, Foyers, Retails Shops, Shopping Centres, Aged Care Facilities, Schools, Offices.

Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers.

*** NOTE: Dimensions and Cut Out sizes may change without notification

RLDR437 SERIES LINEAR RECESSED DOWNLIGHTS

RLDR437 SYMMETRICAL



RLDR437 ASYMMETRICAL



Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers.

*** NOTE: Dimensions and Cut Out sizes may change without notification





Rytec Lighting Australia Pty Ltd



RLDR437 Symmetrical



Cat	System Watt	Lumen Output at 36°	Colour Temperature	Beam Angle	Length x Width x Depth	Cut Out mm
RLDR437-45-4	4W	144 163 194	2700K 3000K 4000K	15°/ 36° 15°/ 36° 15°/ 36°	45 x 45 x 42	37 x 37
RLDR437-76-6	6W	279 326 385	2700K 3000K 4000K	15°/ 36° 15°/ 36° 15°/ 36°	76 X 45 X 51	68 x 37
RLDR437-105-9	9W	427 482 606	2700K 3000K 4000K	15°/ 36° 15°/ 36° 15°/ 36°	105 x 45 x 51	97 x 37
RLDR437-147-13	13W	689 797 943	2700K 3000K 4000K	15°/ 36° 15°/ 36° 15°/ 36°	147 x 45 x 51	139 x 37
RLDR437-280-25	25W	1310 1420 1824	2700K 3000K 4000K	15°/ 36° 15°/ 36° 15°/ 36°	280 x 45 x 51	272 x 37
RLDR437-413-37	37W	2030 2146 2839	2700K 3000K 4000K	15°/ 36° 15°/ 36° 15°/ 36°	413 x 45 x 51	405 x 37
RLDR437-75-11	11W	491 582 714	2700K 3000K 4000K	15°/ 36° 15°/ 36° 15°/ 36°	75 x 75 x 51	67 x 67
RLDR437-105-23	23W	1246 1412 1765	2700K 3000K 4000K	15°/ 36° 15°/ 36° 15°/ 36°	105 x 105 x 51	97 x 97







Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers.

*** NOTE: Dimensions and Cut Out sizes may change without notification



RLDR437 Asymmetrical

Cat	System Watt	Lumen Output at 36°	Colour Temperature	Asymmetrical Beam Angle	Length x Width x Depth	Cut Out mm
RLDR437/AS-105-9	9W	287 321 381	2700K 3000K 4000K	70° x 90° x 10°	105 x 45 x 51	97 x 37
RLDR437/AS-147-13	13W	478 533 696	2700K 3000K 4000K	70° x 90° x 10°	147 x 45 x 51	139 x 37
RLDR437/AS-280-25	25W	931 1044 1301	2700K 3000K 4000K	70° x 90° x 10°	280 x 45 x 51	272 x 37
RLDR437/AS-413-37	37W	1402 1605 2018	2700K 3000K 4000K	70° x 90° x 10°	413 x 45 x 51	405 x 37



Lumen output based on Absolute lumens, 4000K LED chip and manufacturers rated mA drivers.

*** NOTE: Dimensions and Cut Out sizes may change without notification